

# PA Satellitensystem

## LD DAVE 15 G2 - 15" Active Dave PA System

Power Output (RMS): 400W + 2 x 150W



Speakon 2 x 3 Meter



Speakon 2 x 10 Meter

# Monitor

2 x Behringer Eurolive B212D / 550 W



# Mixer

## Soundcraft EPM 8



# Effekt

## Lexicon Alex Halleffekt

<p><b>MIX</b> Controls the proportion of processed (wet) to unprocessed (dry) signals sent to the outputs.</p>	<p><b>OUTPUT</b> Controls Alex's output level.</p>	<p><b>VALUE</b> Adjusts selected parameter.</p>	<p><b>REGISTER/PRESET</b> Button selects preset or register mode. LED lights when register mode is selected, turns off in preset mode. Knob will select presets 1-16 or registers 1-16, depending on button setting.</p>
<p><b>INPUT</b> Sets the level of the incoming signal.</p>	<p><b>PARAMETER</b> Selects DECAY, DELAY or FX LVL for adjustment with the VALUE knob. (Selection indicated by lit LED.)</p>		
<p><b>STORE (+)/CLEAR (-)</b> Toggles the Store and Clear functions. When "+" is displayed, press and hold to store the current effect to displayed register. When "-" is displayed, press and hold to clear a register to allow effects to be skipped for a footswitch step or chain sequence.</p>	<p><b>DISPLAY</b> Numeric display of digits 1-16, and decimal point. Displayed digits indicate ID number of currently running effect or parameter setting if one of parameter LEDs is flashing. Decimal point lights to show an effect has been modified since it was stored.</p>		



1 x PD Connex CX76-1 Klinke 6,3mm, male - Klinke 6,3mm, male 1.5 m

# Mics und Kabel



Mic 2 x Shure SM58

XLR Kabel 5 m + 3 m



3.5 mm to Jack



2 x Jack / Jack



3 x XLR f to Jack



XLR m to XLR f



3 x XLR Kabel 10 m



Multicore 16/4 30 m